


COMPANY:		CONTACT: -----	INW NO:	DATE:
MAKE:	HP/KVA/KW:	POLES:	RPM:	FRAME:
MODEL:	VOLTS:	AMPS:	HZ:	PHASES:
SI NO:	INS.CL :	WEIGHT:		

1	Core Inside Diameter:		FINAL TESTING ON INDIVIDUAL COIL:
2	Core Length:		
3	Finger Plate Width:		
4	Number of Slots:		
5	Number of Coils		
6	Total Slot Depth:		
7	Coil Space under Wedge:		
8	Slot Width:		
9	Slot Skew Left Distance:		
10	Slot Skew Right Distance:		
11	Turns per Coil:		
12	No. of Conductors in Parallel		
13	No. of Section		
14	Copper Size - Width:		
15	Insulated Conductor Size	Width: Thickness:	
16	Conductor thickness in commutor		
17	Riser Width:		
18	Coil Width in Slot:		
19	Coil Width outside Slot:		
20	Straight Length of Coil Side:		
21	Rear Extension:		
22	Distance Between Core and Riser		
23	Coil Pitch:	1 -	
24	Leads Tinned or Not?:		
25	Single or Double Knuckled	A: B:	
26	Minimum Winding Diameter		
27	Front Extension:		
28	Wiring Parallels Please Tick  Other <input type="checkbox"/>		

TRACTION COIL

